

X-Rite®

341 Portable Transmission Densitometer

**A Portable
Densitometer
Capable Of
Measuring Densities
Greater than 5.00**



The 341 Portable Transmission Densitometer concentrates the best features of a tabletop densitometer inside a compact, portable, and economical hand-held unit. We designed the 341 as a completely self-contained instrument able to take measurements anywhere you need.

A Solid Performer

The X-Rite 341 includes a calibrated, internal light source. It meets global standards for geometry of a transmission densitometer, including proper diffusion of the light source, enabling true measurement values.

The 341 measures density and dot area with extraordinary accuracy — in fact, it's capable of measuring densities greater than 5.0D. The model 341 includes a calibration reference that is traceable to ISO standards for transmission densitometry.

Density and Dot Area Applications

The 341 can be used to make dot area and density measurements quickly and easily. The density function is useful for evaluating and setting the exposure of any imagesetter system, positive or negative. Use it to verify the D_{max} of your films, ensuring light-blocking film properties when making proofs or printing plates.

The dot area function is useful for verifying screen tint values from contact films, duplicate films, or originals. It can zero on the film base, and accurately measure from 0 to 100 percent. It is handy and easy to use in linearizing or calibrating the tone value of any imagesetter.

Need More Functionality?

Consider pairing the 341 with our popular 500 Series Spectrodensitometer to create unique capabilities (see side bar). This combined system has the ability to measure solid and screened areas of your images on both film and paper.

The compact and rugged 341 also includes rechargeable Ni-Cad batteries and a power supply, to deliver hours of cordless operation. Also included is a carrying case for storage of the 341 when you travel.



500 Series Spectrodensitometers:

Spectral technology has begun revolutionizing the graphic arts industry. Why? Because it offers significant advantages over existing technologies—primarily, it delivers density and colorimetry in a single instrument.

Spectrally Based

500 Series models feature a high-resolution spectrophotometric engine that supplies the most accurate information available. X-Rite's spectral technology allows the highest level of inter-instrument agreement available today.

Large Interactive Display

Large, crisp graphic display configurable for left- or right-handed operation. Display allows menu commands in multiple languages (English, French, German, Italian, Portuguese and Spanish).

New User Interface

An intuitive key pad uses universally understood up/down arrow keys and a select key to navigate menu items. For efficiency, we also included a "back-up" key and an "escape" key, which takes users back to the main menu.

Upgradeable

All instruments in the 500 Series are firmware upgradeable. You can easily add functionality as your needs change maintaining the value of your investment.

New Ergonomic Design

All of our new hand-held instruments apply ergonomic concepts to fit naturally in your hand. The targeting shoe clearly pinpoints the measurement area so users get the right measurement every time.

Rugged Construction

500 Series instruments absorb the inevitable bumps of everyday use. The 500 Series carries the tradition of the 400 Series as being the most durable instrument in the industry. You get years of reliable performance.

Model 341 Benefits:

- Ideal for all graphic arts film applications, from quality control to calibration.
- Extraordinary accuracy when measuring density and dot area.

- Able to measure densities greater than 5.0D for use with high density linear films.
- Conforms to ANSI PH2.19 and ISO 5/2 standards for transmission densitometry.
- Simple to operate and easy to hold.
- Provides pre-press operators with fast, accurate feedback to verify film quality and minimize waste.
- Can be complemented with X-Rite 500 Series Reflection Densitometer to measure solid and screened areas on both film and paper.
- Backed by X-Rite's world-class service and application support teams.

Model 341 Features:

- Completely self-contained operation. No independent power supply or light source required.
- Built-in light table lets you quickly find the right area for measurement.

- Long-lasting batteries enable you to make hundreds of measurements before recharging the unit.
- Comes with four long-life, rechargeable Ni-Cad AA batteries.
- High-contrast LCD display that is easy to see and easy to use.
- Includes 2mm, and 3mm apertures allowing measurement of a variety of film line screen rulings.
- Directly measures density and percent dot area.

Specifications:

Measuring Range

0 to >5.0D
0% to 100%

Measuring Area

2mm and 3mm

Repeatability

±0.01D (0 to 4.0D)
2mm and 3mm aperture
±1% (4.0D to 5.0D)
3mm aperture

Warm-Up Time

None

Linearity (Accuracy)

±0.02D (0 to 4.0D)
2mm and 3mm aperture
±2% (4.0D to 5.0D)
3mm aperture

Zero Stability

±0.02D (0.01 typical)

Response

ANSI/ISO visual

Measuring Length (Throat)

5.5 inches (14cm)

Power Supply

4 rechargeable AA Ni-Cad batteries (included)
AC adapter (included)

AC Adapter Requirements

341: 90-130 VAC, 50-60 Hz, 1500 max.
341x: 180-260 VAC, 50-60 Hz, 1500 max.

Operating Temperature Range

50° to 104°F (10° to 40°C)

Physical Dimensions

2.0" H (5.08 cm)
2.9" W (7.46 cm)
7.0" L (17.78 cm)

Weight

1.52 lbs. (690 g)

Safety & Compliance

UL, CUL
CE
FCC Class A



www.x-rite.com

ISO 9001
Certified

X-Rite, Incorporated – World Headquarters 3100 44th Street SW • Grandville, Michigan 49418 USA • (616) 534-7663 • (800) 248-9748 • FAX (616) 534-8960

X-Rite Ltd. The Acumen Centre • First Avenue • Poynton, Cheshire • United Kingdom SK12 1FJ • 44 (0) 1625 871100 • FAX 44 (0) 1625 871444

X-Rite Méditerranée Parc du moulin de Massy • 35, rue du Saule Trapu • 91300 Massy • France • 33 1-69.53.66.20 • FAX 33 1-69.53.00.52

X-Rite Asia Pacific Ltd. Room 808-10 • Kornhill Metro Tower • 1 Kornhill Road • Quarry Bay • Hong Kong • (852) 2-568-6283 • FAX (852) 2-885-8610

X-Rite Asia Pacific Ltd. Japan Office • 7F, IMAS Hamamatsu-cho Bldg. • 2-10-4, Hamamatsu-cho, Minato-ku • Tokyo 105-0013 Japan • 81-3-5777-5488 • FAX 81-3-5777-5489

X-Rite GmbH • Stollwerckstr. 32 • 51149 Köln • Germany • (49) 2203-91450 • FAX (49) 2203-914519

X-Rite GmbH Czech Office • Sochorova 705 • CZ-682 11 Vyskov • Czech Republic • (420) 507-328197 • FAX (420) 507-328138

©X-Rite, Incorporated 2001. Specifications and design subject to change without notice. X-Rite® is a registered trademark of X-Rite, Incorporated. Products manufactured by X-Rite, Incorporated are warranted to be free from defects in material and workmanship under normal use and service, for a period of twelve (12) months from the date of shipment. X-Rite, Incorporated will repair or replace, at its option, Products which prove to be defective within the warranty period, that are returned F.O.B. its factory. X-Rite, Incorporated's warranty shall be voided by any repair, alteration, or modification by persons other than the employees of X-Rite, Incorporated, or those expressly authorized

by X-Rite, Incorporated to make repairs, and by any abuse, misuse or neglect of the Products, or by use not in accordance with X-Rite, Incorporated's published instructions. The remedies for any failure of X-Rite, Incorporated's Products to meet its warranty specified herein shall be those remedies stated herein and no others; these remedies being exclusive remedies as a condition of sale. EXCEPT AS PROVIDED IN THIS PARAGRAPH, X-RITE, INCORPORATED MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE.